
This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS							
REV	DESCRIPTION	DATE	INITIAL	APPROVED			
1	AS DRAWN BY APICAL	6/14/2013	CFS				
2	CH'D SPRING MATERIAL THICKNESS WAS .031 IS .041.	5/20/2014	RJC	PW			





_								
	® RED BARN MACHINE							
	CLOCK SPRING							
ĺ	DWG NO. PC250-800 REV 2							
[MAT'L 301 S.S.			DR	AWN BY:	APICAL		
		THERWISE S ONS ARE IN I FRACTIO ANGL	INCHES	HE	AT	D Wei HRC 40-46	e	
\dashv	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING			• —	SPEC USED ON MODEL			
				`_				
ヿ	SCALE 1:	1 D	ATE	9/2/2	009	SHEET 1	OF 1	

ASSY QTY	ASSY QTY	В/О	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS
		B/O	PC250-800	1	CLOCK SPRING	301 S.S.	.041 X 1-1/4 X 38-3/4 DENDOFF